

**RANDOLPH COMMUNITY
COLLEGE**

**HEARING CONSERVATION
PROGRAM**

Reviewed May 2010

1. PURPOSE

The purpose of this program is to provide guidelines for employees exposed to occupational noise and to comply with the OSHA Occupational Noise Exposure Standard 29 CFR 1910.95.

The objective of the procedure is to provide guidelines to protect the hearing of those employees exposed to noise levels in excess of 85 dBA, to provide a uniform method of dealing with noise and hearing conservation for all departments, and to develop historical data.

2. SCOPE

All employees exposed to an 8-hour time-weighted average (TWA) of 85 dBA or greater shall be included in this program.

The Hearing Conservation Program consists of the following components:

- a. Noise Level Monitoring and Evaluation
- b. Noise Control
- c. Audiometric Testing
- d. Hearing Protection
- e. Employee Training

3. NOISE LEVEL MONITORING AND EVALUATION

Noise Level Monitoring

Monitoring of noise exposure levels shall be conducted to accurately identify employees who are exposed to noise levels at or above 85 dBA, averaged over eight working hours; this is called an 8-hour time-weighted average (TWA). The exposure measurement shall include all sound levels within an 80 dBA to 130 dBA range, and shall be taken during a typical work situation. Measurements shall be obtained on the A scale of a standard sound level meter at slow response.

Note: Where high worker mobility or significant variations in sound level make area monitoring generally inappropriate, representative personal sampling (dosimetry) shall be conducted.

Monitoring shall be repeated whenever a change in the process, equipment, or controls is suspected of increasing noise exposures to the extent that additional employees may be exposed to noise levels at or above 85 dBA as an 8-hour TWA, or when the attenuation provided by the selected hearing protective devices is rendered inadequate. This re-evaluation of work place noise shall be conducted within 60 days following the aforementioned changes.

Employees are entitled to observe the monitoring procedures.

Review of all employee complaints concerning noise shall be conducted within 60 days by:

- a. In-house screening of noise levels with a sound level meter.
- b. Conducting noise dosimetry on affected employees.

Noise Exposure Evaluation

Upon completion of a noise level monitoring of an area, noise dosimetry shall be conducted on those employees potentially exposed to levels of noise in excess of an action level of 85 dBA or greater. (Personnel noise dosimetry shall be conducted by job description.)

Noise dosimeters shall be capable of integrating all continuous, intermittent, and impulsive sound levels from 80 decibels to 130 decibels.

All sound level meter reading and octave band analyses that represent employee exposure shall be maintained on file at least 30 years in accordance with 1910.1020(d)(1)(ii).

Each employee exposed at or above an 8-hour TWA of 85 dBA shall be notified of the results of the monitoring. The normal method of notification is posting the results in a visible location.

4. NOISE CONTROL

Noise control can be addressed by three main categories: engineering controls, administrative controls, and personal hearing protection. This section will address the first two controls.

The most desirable method of noise control is to apply engineering principles designed to reduce sound levels either at the source or within the hearing zone of the employee. This application can usually reduce noise to a desired level, however economic considerations and/or operational necessities can make these controls impractical. It is the college's policy to utilize engineering controls whenever feasible and practical to reduce employee noise exposures.

Whenever engineering controls are not feasible or practical, the use of administrative controls should be explored. (Note: Administrative controls may be used in conjunction with engineering controls.) Administrative controls include any administrative decision that results in lower noise exposures; including complying with purchase agreements that specify maximum noise levels for machinery.

Administrative controls may include rotating jobs so that exposure times are reduced. This includes such measures as transferring employees from a location with high noise levels to one with a lower level in order to reduce the daily exposure below the "action level". When administrative controls are not feasible with regard to job rotation, other alternatives, including hearing protection (See Section 6.0) will be utilized to reduce the daily noise exposure.

It is the college's policy to use administrative controls whenever practical to reduce employee noise exposure.

5. AUDIOMETRIC TESTING

Wendy Laing 2/6/02 2:49 PM

Deleted: -

Criteria for Audiometric Testing

Audiometric testing monitors the sharpness or acuity of an employee's hearing over time, and provides an opportunity for employers to educate employees about their hearing and the need to protect it.

A baseline audiogram is the reference audiogram against which future audiograms are compared. Baseline audiograms shall be conducted for new hires that will work in areas with high levels of noise within 6 months. Any employees whose job contains exposure to an 8-hour time-weighted average (TWA) of 85 dBA shall be included in the baseline audiogram.

The annual audiogram shall be conducted within one year of the baseline. It is important to test hearing on an annual basis in order to identify changes in hearing ability. Annual audiograms shall be routinely compared to baseline audiograms to determine whether the audiogram is accurate and to determine whether the employee has a change in hearing ability (that is, if a standard threshold shift (STS) has occurred).

STS is defined as an average shift in either ear of 10 dBA or more at 2,000, 3,000, and 4,000 Hz. An averaging method of determining STS was chosen because it diminishes the number of persons falsely identified as having STS who are later shown not to have had a change in hearing ability.

The annual audiogram shall be conducted for all employees who are exposed to noise levels equal to or in excess of an 8-hour time-weighted average (TWA) sound level of 85 dBA measured on the A scale. Employees who have the baseline audiogram conducted as a new hire shall receive an annual audiogram.

A work history/hearing questionnaire is required on each employee tested. This questionnaire shall be updated with each annual test.

Annual Hearing Test Guidelines

The annual audiogram shall be preceded by 14 hours without exposure to workplace noise; however, hearing protectors may be used as a substitute for this practice.

An annual work history/hearing questionnaire is required.

The audiometric examination shall be conducted by a certified audiometric technician (CAOHC), a trained physician, or a licensed or certified audiologist.

The audiometer shall be acoustically calibrated annually in accordance with Appendix E of 29 CFR 1910.95. The audiometric examination shall be conducted in a booth/room meeting the criteria outline in 29 CFR 1910.95, Appendix, Table D-1. The booth/room shall have accurate sound level measurements made at least annually, using a Type 1 octave band analyzer/sound level meter.

If an employee has a STS when exposed to noise at or above the action level, the following items shall be reviewed:

- a. Employees shall be notified within 21 days from the time the determination is made that their audiometric test results showed a STS.
- b. A retest may be obtained within 30 days and the results of the retest can be considered as the annual audiogram.
- c. Employees not using hearing protectors shall be fitted with hearing protectors, trained in their use and care, and required to use them.
- d. Employees already using hearing protectors shall be refitted and retrained in the use of hearing protectors and provided with hearing protectors offering greater attenuation if necessary.
- e. Some employees with a STS may need to be referred for further testing if the professional determines that their test results are questionable or if they have an ear problem of a medical nature which is thought to be caused or aggravated by wearing hearing protectors. If the suspected medical problem is not thought to be related to wearing protectors, employees must be informed that they should see a physician.
- f. A subsequent audiogram may be substituted for the original baseline audiogram if the professional supervising the program determines that the employee's STS is persistent. This substitution will ensure that the same shift is not repeatedly identified. The professional may also decide to revise the baseline if an improvement in hearing has occurred. This will ensure that the baseline reflects actual hearing thresholds to the extent possible.

Post-test Guidelines

All audiograms will be reviewed by the company's consulting occupational physician or audiologist.

6. HEARING PROTECTION

Hearing protective devices (HPD) shall be readily available at no cost to all employees exposed to an 8-hour time-weighted average of 85 dBA or greater, and to employees that enter an area

or perform a task requiring hearing protection. Appendix A lists the locations and tasks at the college that require hearing protection.

HPDs must be worn by:

- a. All employees exposed to an 8-hour TWA of 85 dBA or greater.
- b. Any employee entering an area in which hearing protection is required, where noise levels are 85 dBA or greater.
- c. Any employee performing a task in which hearing protection is required, where noise levels are 85 dBA or greater.

The employees shall have an opportunity to select their HPDs from at least 2 different styles. Each department that shall supply the HPDs.

HPDs shall be evaluated to ensure that they attenuate noise level exposures to less than 90 dBA. For employees who have experienced a standard threshold shift, hearing protectors shall attenuate employee exposure to an 8-hour TWA of 85 dBA or below.

7. TRAINING

Annual training is required for all employees who are exposed to noise at or above an 8-hour TWA of 85 dBA.

Information provided in the training program shall be updated to be consistent with changes in protective equipment and work process.

Each employee shall be informed of the following:

- a. The effects of noise on hearing.
- b. The purpose of hearing protection, the advantages, disadvantages, and attenuation of various types, the instruction on selection, care and use.
- c. The purpose of audiometric testing and explanation of the test procedure.

The Director of Safety is responsible for maintaining all training documentation.

8. RECORDKEEPING

Audiometric test records shall be retained on all employees and maintained for 30 years after employment ceases. The records shall be maintained with the college Director of Safety and Emergency Preparedness or at another designated storage location. The record shall include:

- a. Name
- b. Job title
- c. Date of audiogram
- d. Examiner's name
- e. Make and model of audiometer

- f. Calibration date of audiometer
- g. Most recent noise exposure assessment (in accordance with 1910.95(m)(2)(ii)(E))

Noise exposure monitoring records shall be maintained in accordance with 1910.1020(d)(ii).
The college Safety Director will maintain these records.

Employees who suffer a STS will be recorded on the OSHA Form 300 Injury and Illness Log as required by 29 CFR 1904.7.

9. REVIEW OF HEARING CONSERVATION PROGRAM

An annual audit of the Hearing Conservation Program shall be conducted by the college Safety Committee

APPENDIX A

AREAS REQUIRING HEARING PROTECTION

Noise areas requiring hearing protection, which have been defined by noise level monitoring, shall have an adequate number of signs requiring the wearing of hearing protectors. Disposable hearing protectors shall be provided at these locations.

The following areas require hearing protection:

**Checked by EHSI representatives on 12/12/2008
3 areas found to be in excess of the standard**

Auto Body Repair

Grounds keepers (Mowers)

ESTC Firing Range